



Kontinuerligt / Continuous  
 Max arbejdstryk / : 5 MPa (50bar)  
 Max working pressure  
 Intermittert  
 Max arbejdstryk / : 5MPa (50bar)  
 Max working pressure  
 Provetryk / : 10 MPa (100bar)  
 Test pressure  
 Tølningsrets cylinder / :  
 Seal kit cylinder  
 Inmetallic detaljer markerede TS i styklisten /  
 Contains details marked TS in the partlist.

18	1	3 779 628	Skriv	MFSS 6x12
17	1	3 779 629	Brækk	
16	1	9127 1491	Værningskylt	
15	1	9128 8383	Målestykke	
14	1	3 779 579	Kolveståbe	
13	2	0665 9099 10	Åsentråkke	TS
12	2	3 779 582	A-lock	
11	4	0665 0700 42	Kolvestøbtåbe	TS
10	2	0661 1500 65	Siddring	TS
9	1	0663 2135	O-ring	TS
8	1	0663 6123	O-ring	TS
7	1	0665 0032 06	Kolveståbe	TS
6	1	0665 9300 10	Sivring	TS
5	1	3 779 581	Kolv	
4	1	3 779 575	Montel	
3	6	1 9125 7098 00	Skriv	MGSS 8x30
2	1	3 779 580	Kolveståbe	
1	1	3 779 577	SKV8507	

02	---	+/±, +/-, +/-, +/-	99147	99-09-30.5300K/8d	
01	---	-/02/11 7201 03+1923 7098 00/+ pøse 17-18/	99135	99-09-23.5300K/1d	
00	---	-/07/08-1410K/-34+30/-7mm+27mm/	99008	99-09-10.5300K/1d	
Kit	Pos	Indhold	Køb nr	Datum	Underskr

Benævnelser:  
 Cylinder til hyd. styring (50x32-240)

Sign:	MA	Dato:	06-09-99	Materialer:	1:2	Versioner:	000
-------	----	-------	----------	-------------	-----	------------	-----

Tegningsnr.: 10A0186

Xref RAN5012

