

Kontinuerligt / Continuous  
 Max arbejdstryk / Max working pressure : 5MPa (50bar)  
 Intermitterent / Intermittent  
 Max arbejdstryk / Max working pressure : 5MPa (50bar)  
 Prøvetryk / Test pressure : 10 MPa (100bar)

Tølningsrets cylinder / Seal kit cylinder  
 Innehåller detaljer markerade TS i avtydningen / Contains details marked TS in the portrait.


Pos	Ant	Part nr	Material	Specifikation	Handling/Note
14	1	9127 1491			
13	1	9128 8363		Varningskylt	
12	1	3 779 571		Køvetåning	
11	2	0665 9099 10		Asterkøre	TS
10	2	3 779 574		A-look	
9	4	0665 0700 42		Køvetåning	TS
8	2	9124 9642		Sikdråne	TS
7	2	0663 6135		O-ring	TS
6	1	0663 6123		O-ring	TS
5	1	3 779 573		Køvetåning	TS
4	1	0665 0700 37		Køvetåning	TS
3	1	0665 9300 04		Sikdråne	TS
2	1	3 779 568		Køvetåning	TS
1	1	3 779 572		Køvetåning	TS

Art	Pos	Part nr	Material	Specifikation	Handling/Note
02	1	9917			
01	1	99135			
00	1	9908			

**Bemærkning:**  
 Cylinder til hyd. styring (63x32-120)

Sign.: MA  
 Dato: 06-09-99  
 Tegningssk.: 1:2  
 Versionssk.: 000

Materiale: 10A0187



46 16 10 72

Xref RAMSOL2